


INSTALLATION

FIXTURES - FLEXIBLE - ZALA




WHITE SNUG CLIP


NOTE: White Snug Clip spacing every 12"




INCLUDED HARDWARE




#6x5/8 Flat Head Screw



Mount White Snug Clip with provided flat head screw.




Align fixture to White Snug Clips matching distances.




Press fixture into White Snug Clips.

MAGNETIC CLIP


NOTE: Magnetic Clip spacing every 12"




INCLUDED HARDWARE




#6x5/8 Flat Head Screw



Install magnet rings with provided flat head screw.



Attach Clips to fixture matching magnet distances.



Align and snap fixture to magnetic rings.


INSTALLATION

FIXTURES - FLEXIBLE - ZALA




RIGID LOCK CHANNEL


NOTE: Rigid Lock Channel spacing every 12"




INCLUDED HARDWARE



Mount Rigid Lock Channel with provided flat head screw.




Push Retainer Clip onto fixture.
Push fixture with Retainer Clip into Rigid Lock Channel.





Tighten Set Screw to lock fixture in Channel for extra security.

SIDE GRAZE CHANNEL


NOTE: Side Graze Channel spacing every 12"




INCLUDED HARDWARE



Remove cover, Install Side Graze Channel with provided #6x5/8 Flat Head Screw.



Press fixture into Side Graze Channel.



Snap screw cover onto Side Graze Channel to hide screws.


INSTALLATION

FIXTURES - FLEXIBLE - ZALA




PVC MOUNT CLIP: Connects two seamless fixtures, with or without wire exit


ZALA-PPS - 2



Mounting Feed (Shown: S5, S6 & P5, P6)




Press both fixtures into PPS clip.




Snap fixture into mounted PPS channel

- When wire will exit into conduit do not install bracket.




LOW PROFILE PVC MOUNT CLIP: Connects two fixtures, no wire exit


ZALA-PPS - LP - 2




Mounting Feed (Shown: S1 & P1)



Snap in 2" channel



Press in fixtures




INSTALLATION

FIXTURES - FLEXIBLE - ZALA




PVC MOUNT CHANNEL: Support for the fixture

ZALA-PPS - 96 & ZALA-PPS - FT




- 96" (PPS-96) or custom length (PPS-FT)

INCLUDED HARDWARE




PPS - BRACKET:
Sold in full length of 96"
or custom length (FT)




#8 Flat head screw

Built in wireway:


The PPS-BRACKET allows you to create a wire way under the PPS channel without any screws interfering



Cove install





1.



The PPS-BRACKET can be field cuttable and cut to whatever length your application requires. The PPS-BRACKET can be installed as a full length of 96", multiple smaller pieces, or end to end for longer seamless runs.

2.




#8 Flat Head Screw

Using pre-drilled pilot holes screw the #8 flat head screws to mount the PPS-BRACKET (1 screw every 16").


NOTE : For drywall applications mount directly into a stud.

3.




Using pre-drilled pilot holes, use the #8 flat head screws to mount the PPS-BRACKET.

4.



The PPS-96 or PPS-FT can be field cuttable and cut to whatever length your application requires. The PPS-96 or PPS-FT can be installed as a full length of 96", multiple smaller pieces, or end to end for longer seamless runs.

5.



To mount, pinch the upper half of the PPS-96 or PPS-FT while you pivot it around one side of the PPS-BRACKET and push-in until you hear it snap into place. The PPS-96 or PPS-FT flexes around the PPS-BRACKET to create a solid, and secure snap on connection.


INSTALLATION

FIXTURES - FLEXIBLE - ZALA




LOW PROFILE PVC MOUNT CHANNEL: Support for the fixture

ZALA-PPS-LP-96 & ZALA-PPS-LP-FT




- 96" (PPS-LP-96) or custom length (PPS-LP-FT)



INCLUDED HARDWARE




PPS - BRACKET:
Sold in full length of 96"
or custom length (ft)



#8 Flat head screw




The PPS-BRACKET can be field cuttable and cut to whatever length your application requires. The PPS-BRACKET can be installed as a full length of 96", multiple smaller pieces, or end to end for longer seamless runs.




Using pre-drilled pilot holes screw the #8 flat head screws to mount the PPS-BRACKET (1 screw every 16").


NOTE : For drywall applications mount directly into a stud.



Using pre-drilled pilot holes, use the #8 flat head screws to mount the PPS-BRACKET.



The PPS-LP-96 or PPS-LP-FT can be field cuttable and cut to whatever length your application requires. The PPS-LP-96 or PPS-LP-FT can be installed as a full length of 96", multiple smaller pieces, or end to end for longer seamless runs.



To mount, pinch the upper half of the PPS-LP-96 or PPS-LP-FT while you pivot it around one side of the PPS-BRACKET and push-in until you hear it snap into place. The PPS-LP-96 or PPS-LP-FT flexes around the PPS-BRACKET to create a solid, and secure snap on connection.