



# WURM-SW FIXTURES - FLEXIBLE (Q-CAP)



PRODUCT	MOUNTING	RATED	CCT	OUTPUT	LENS	TYPE	CONNECTOR/ WIRE IN	CONNECTOR/ WIRE OUT	END CAPS (NO FEED)	LENGTH (IN)
<b>WURM-SW</b> Voltage: 24 VDC Wattage: see table	<b>WSCS</b> <b>MCS</b>	<b>DRY</b> <b>WET</b>	<b>24</b> - 2400K <b>27</b> - 2700K <b>30</b> - 3000K <b>35</b> - 3500K <b>40</b> - 4000K	<b>SO</b> <b>HO</b> <b>VHO</b>	<b>ENC/CL</b> <b>ENC/TL</b>	<b>S1</b> <b>P1</b>	<b><sup>1</sup>BW</b> <b>BRL</b>	<b>N/A</b> <b><sup>1</sup>BW</b> <b>BRL</b>	<b>WH</b> <b>N/A</b>	1" increments from 1"-191"  Tolerance +0.0"/-outpoint for installed product*

ENCAPSULATED PRODUCTS ARE NOT FIELD CUTTABLE

- NOTES:**
- Field modifications are not covered under Q-Tran warranty
  - Data subject to change, all data has +/- 5% tolerance
  - PPS-FT** is to be cut at Q-Tran at requested foot length
  - <sup>1</sup>BW comes in standard 24"- request custom length (Max 120") by writing it in inches next to "BW" in the order code box (ex. BW48)
  - Connector/Wire In or Out not needed to specify product. Standard configuration is Type S1, Connector/Wire In: BW & Connector/Wire Out: N/A with White Endcap (WH)

## OUTPUT Tested for WURM-SW-WSCS-DRY [L70 = 40000 hrs]

CCT	SO Standard Output 1.5 W/ft				HO High Output 3.0 W/ft				VHO Very High Output 5.0 W/ft			
	ENC/CL		ENC/TL		ENC/CL		ENC/TL		ENC/CL		ENC/TL	
	LM	CRI	LM	CRI	LM	CRI	LM	CRI	LM	CRI	LM	CRI
2400K	127	94	107	94	231	93	189	93	329	94	274	94
2700K	127	97	103	97	227	98	197	98	329	98	273	98
3000K	135	99	110	98	242	98	202	98	337	98	267	97
3500K	144	96	115	96	242	96	201	97	359	97	304	97
4000K	151	96	126	96	262	96	218	96	370	97	316	97

## LENS with LED visibility

ENC/CL	ENC/TL
Encapsulated in Clear	Encapsulated in Translucent

NOTE: Indirect view recommended

## CONNECTOR/WIRE IN


<sup>1</sup> BW	BRL	<sup>1</sup> BW	BRL
Bare wire 24"	Barrel 6"	Bare wire 24"	Barrel 6"

## CONNECTOR/WIRE OUT

**MOUNTING** NOTE: 2 white snug clips provided per first 12", 1 for each additional 12". Other mounting styles incur additional charge, see price guide for details.

WSCS	MCS
White Snug Clip Small	Magnetic Clip Small (Cove use only)


## FLEXIBILITY



Up/Down & Helical\*


\*Max recommended rotation of 1 rotation per 16"

## DIMENSIONS




## TYPE


SINGLE (Input only)




PASS THROUGH (Input/Output)




ORDER EXAMPLE



## END CAPS (NO FEED)



## END CAPS (WITH FEED)



PROJECT NAME	DATE	COMPANY	TYPE	NOTE