



WURM-DW FIXTURES - FLEXIBLE (Q-CAP)



PRODUCT	MOUNTING	RATED	CCT	OUTPUT	LENS	TYPE	CONNECTOR/ WIRE IN	CONNECTOR/ WIRE OUT	END CAPS (NO FEED)	LENGTH (IN)
WURM-DW Voltage: 24 VDC Wattage: 3.0 W/ft Per Channel 6.0 W/ft Total Load	WSCS MCS	DRY WET	24/30 24/30	HO HO	ENC/CL ENC/TL	S1 P1	BW 1BW	N/A 1BW	WH N/A	2" increments from 2'-191" Tolerance +0.0"/-cutpoint for installed product*


ENCAPSULATED PRODUCTS ARE NOT FIELD CUTTABLE

- NOTES:**
- Field modifications are not covered under Q-Tran warranty
 - Data subject to change, all data has +/- 5% tolerance
 - PPS-FIT** is to be cut at Q-Tran at requested foot length
 - 1** BW comes in standard 24"- request custom length (Max 120") by writing it in inches next to "BW" in the order code box (ex. BW48)
 - Connector/Wire In or Out not needed to specify product. Standard configuration is Type S1, Connector/Wire In: BW & Connector/Wire Out: N/A with White Endcap (WH)

OUTPUT Tested for WURM-DW-WSCS-DRY [L70 = 40000 hrs]

CCT	HO High Output				Circuit Wattage
	ENC/CL		ENC/TL		
	LM	CRI	LM	CRI	
2400K	212	93	168	92	2.93
3000K	221	96	180	96	2.93

LENS with LED visibility




NOTE: Indirect view recommended


CONNECTOR/WIRE IN




CONNECTOR/WIRE OUT



MOUNTING NOTE: 2 white snug clips provided per first 12", 1 for each additional 12". Other mounting styles incur additional charge, see price guide for details.




FLEXIBILITY



Up/Down & Helical*


*Max recommended rotation of 1 rotation per 16"

DIMENSIONS




TYPE

SINGLE (Input only)




PASS THROUGH (Input/Output)



ORDER EXAMPLE




END CAPS (NO FEED)



WHITE ENDCAPS
.11" added at end
.24" dim spot

END CAPS (WITH FEED)



WHITE ENDCAPS
.0" added at end
.38" dim spot

PROJECT NAME	DATE	COMPANY	TYPE	NOTE