

KURV-RGB FIXTURES - FLEXIBLE (Q-CAP)



PRODUCT	MOUNTING	RATED	CCT	OUTPUT	LENS	TYPE	CONNECTOR/ WIRE IN	CONNECTOR/ WIRE OUT	END CAPS (NO FEED)	LENGTH (IN)
KURV-RGB			RGB	SO			BW			
Voltage: 24 VDC Wattage: 2.0 W/ft Per Channel 6.0 W/ft Total Load *White Snug Clip included with Side Graze Channel	WSC RLC MC *SGC PPS-2 PPS-96 PPS-FT PPS-LP-2 PPS-LP-96 PPS-LP-FT	DRY WET	RGB RGB	SO SO	ENC/CL ENC/TL	Single (Closed exit) S1 S2 S3 S4 Pass through P1 P2 P3 P4	1BW 1BW	N/A 1BW	CL WH N/A	2" increments from 2'-191"


ENCAPSULATED PRODUCTS ARE NOT FIELD CUTTABLE

- NOTES:**
- Field modifications are not covered under Q-Tran warranty
 - Data subject to change, all data has +/- 5% tolerance
 - PPS-FT** is to be cut at Q-Tran at requested foot length
 - 1** BW comes in standard 24"- request custom length (Max 120") by writing it in inches next to "BW" in the order code box (ex. BW48)
 - Connector/Wire In or Out not needed to specify product. Standard configuration is Type S1, Connector/Wire In: BW & Connector/Wire Out: N/A with White Endcap (WH)


OUTPUT Tested for KURV-RGB-WSC-DRY [L70 = 40000 hrs]

CCT	SO Standard Output				Circuit Wattage
	ENC/CL		ENC/TL		
	lm/ft	Wavelength	lm/ft	Wavelength	
Red	78	630	71	631	2.4
Green	152	521	135	523	1.9
Blue	46	468	41	469	1.7
All	255		229		6.0


LENS with LED visibility



CONNECTOR/WIRE IN



CONNECTOR/WIRE OUT




MOUNTING NOTE: 2 white snug clips provided per first 12", 1 for each additional 12". Other mounting styles incur additional charge, see price guide for details.


WSC White snug clip	RLC Rigid lock channel	MC Magnetic clip (Cove use only)	SGC Side graze channel
PPS-2 PVC mounting clip	PPS-96 PPS-FT Custom length PVC channel	PPS-LP-2 Low profile PVC mounting clip	PPS-LP-96 PPS-LP-FT Custom length Low profile PVC channel

TYPE


SINGLE (Input only)




PASS THROUGH (Input/Output)




ORDER EXAMPLE




DIMENSIONS




VIEWING ANGLE



FLEXIBILITY




END CAPS (NO FEED)



CLEAR ENDCAPS
.0" added at end
.00" dim spot

WHITE ENDCAPS
.0" added at end
.10" dim spot

END CAPS (WITH FEED)



End feed
S1, P1
WHITE ENDCAPS
.0" added at end
.10" dim spot

Tri-Directional
S2, S3, S4, P2, P3, P4
WHITE ENDCAPS
.32" added at end
.42" dim spot

PROJECT NAME	DATE	COMPANY	TYPE	NOTE