



WURM-RGB FIXTURES - FLEXIBLE (Q-CAP)



| PRODUCT | MOUNTING | RATED | CCT | OUTPUT | LENS | TYPE | CONNECTOR/ WIRE IN | CONNECTOR/ WIRE OUT | END CAPS (NO FEED) | LENGTH (IN) |
|--|---------------------------|--------------------------|--------------------------|------------------------|--------------------------------|------------------------|------------------------|-------------------------|-------------------------|--|
| WURM-RGB Voltage: 24 VDC Wattage: 2.0 W/ft Per Channel 6.0 W/ft Total Load | WSCS MCS | DRY WET | RGB RGB | SO SO | ENC/CL ENC/CL | S1 P1 | BW BW | N/A BW | WH N/A | 2" increments from 2"-191" Tolerance +0.0"/-outpoint for installed product* |

ENCAPSULATED PRODUCTS ARE NOT FIELD CUTTABLE

- NOTES:**
- Field modifications are not covered under Q-Tran warranty
 - Data subject to change, all data has +/- 5% tolerance
 - 1** BW comes in standard 24" - request custom length (Max 120") by writing it in inches next to "BW" in the order code box (ex. BW48)
 - Connector/Wire In or Out not needed to specify product. Standard configuration is Type S1, Connector/Wire In: BW & Connector/Wire Out: N/A with White Endcap (WH)

OUTPUT Tested for WURM-RGB-WSCS-DRY [L70 = 40000 hrs]

| CCT | SO Standard Output | | |
|-------|-----------------------|------------|--------------------|
| | ENC/CL lm/ft | Wavelength | Circuit Wattage |
| Red | 94 | 630 | 2.4 |
| Green | 177 | 523 | 1.9 |
| Blue | 54 | 469 | 1.7 |
| All | 308 | | 6.0 |

LENS with LED visibility


ENC/CL



NOTE: Indirect view recommended

CONNECTOR/WIRE IN


1 BW



Bare wire 24"


CONNECTOR/WIRE OUT

1 BW




Bare wire 24"

MOUNTING NOTE: 2 white snug clips provided per first 12", 1 for each additional 12". Other mounting styles incur additional charge, see price guide for details.



FLEXIBILITY



Up/Down & Helical*

*Max recommended rotation of 1 rotation per 16"

DIMENSIONS




Profile (Standard)

TYPE


SINGLE (Input only)

S1




PASS THROUGH (Input/Output)

P1




ORDER EXAMPLE



END CAPS (NO FEED)


WH



WHITE ENDCAPS
.11" added at end
.24" dim spot

END CAPS (WITH FEED)

End Feed
S1, P1



WHITE ENDCAPS
.0" added at end
.38" dim spot

| PROJECT NAME | DATE | COMPANY | TYPE | NOTE |
|--------------|------|---------|------|------|
| | | | | |